

CONCEPTUAL SITE MODEL (not to scale)







NOTE:

FOR ILLUSTRATION PURPOSES ONLY. THE EXACT LOCATION OF EXTRACTION POINTS IN RESIDENCE BASEMENTS WILL BE DETERMINED AT THE TIME OF INSTALLATION.

VAPOR MITIGATION SYSTEM SCHEMATIC -ELEVATION VIEW SCALE: N.T.S.





NOTES:

TUBING: 1/4" OD STAINLESS STEEL

ELBOWS: SWAGELOK UNION ELBOW 1/4" STAINLESS STEEL

DETAIL 2 — CROSS—SLAB DIFFERENTIAL PRESSURE MEASUREMENT APPARATUS

DETAIL 1 - FAN AND PIPING DETAIL

SCALE: N.T.S.



Photo 1 – Indoor view of sub-slab and indoor air probes



Photo 2 – Another indoor view of the indoor and sub-slab tubing showing the full sub-slab probe.




Photo 3 – Outdoor view of the indoor and sub-slab probes. These probes are for taking differential pressure measurements to make sure the system is working. They can also be used to take soil vapor and indoor air samples from outside of the residence.




Photo 4 – View of the fan and piping. The gate valve isolates the piping such that a soil vapor sample can be collected prior to the fan.




Photo 5 – View of the gutter downspout projecting up the side



Photo 6 – Outside view of the finished product





Figure 1. Remediation Areas / Dissolved Oxygen Concentrations in Shallow Wells, 2004-2005






Figure 3 Independent Remediation System in alley of Area B

